

MODEL 852-2000



Special calender for pieces or continuous fabrics, used for :

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

1. Characteristics of printing cylinder:

- 1.1. Diameter : 200 mm (7,87").
- 1.2. Width : 2.000 mm (70,87").
- 1.3. Working Width: 1.600 mm (62,99") / 1.800 mm (70,87").

2. Heating system and temperature control:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by touch screen and regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. Tension controls:

- 3.1. Tension control for printing material in roll:
 - Entry: brake with manual adjustment
 - Exit: winding with pneumatic device
- 3.2. Tension control for printing paper in roll:
 - Entry: disk brake with pneumatic adjustment
 - Exit: winding with pneumatic device
- 3.3. Tension control for protection paper:
 - Entry: disk brake with pneumatic adjustment
 - Exit: winding with pneumatic device

4. Other devices into machine:

- 4.1. Short front working table, 800 mm
- 4.2. Conveyor belt for automatic discharge on the back of the machine
- 4.3. Single motor
- 4.4. NOMEX felt with pneumatic tension adjustment system and automatic felt-centering device

All data and technical features are purely indicative and subjected to changes without prior notice



MODEL 852-2000



4.5. Incorporated system of felt protection in case of black out and/or compressed air lack

5. Technical data:

5.1. Installed power: 14 kw/h

5.2. Average electric consumption: 9 kw/h

5.3. Compressed air pressure: 3 - 8 bar

5.4. Mechanic speed: 0.1 - 1.7 m/min

5.5. Overall dimensions (with front table): width 3.080 mm (121,25"). length 2.035 mm (80"). height 1.425 mm (56").

5.6. Net weight: 1.450 kg

5.7. Machine produced according to CE rules

5.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice

Monti Antonio S.p.A.
Via dell'Elettronica n°5
36016 Thiene (VI) - Italy

Tel. +39 0445 364619
Fax. +39 0445 364033
sales@montiantonio.com
www.montiantonio.com

STANDARD & CUSTOM HEATING SOLUTIONS



LAMINATING



PRINTING



FINISHING



PRESSING



STEAM GENERATORS